

Series HSL LXT LED: 2X2 & 2X4

Recessed Center Lens LED Troffer

HSL LXT 2X2 & 2X4



FEATURES & SPECIFICATIONS

INTENDED USE

The HSL LXT Series LED fixture has high transmission center lenses. The HSL LXT offers a clean yet subtle appearance and highlights any environment with lines of light providing soft and efficient light output. Due to this unique LXT design with 2 lenses, this fixture will enhance any space, and it is ideal for: commercial/industrial buildings, schools, hospitals, offices and retail.

The extruded high transmission acrylic lens allows for the right brightness without the harsh effects of direct LEDs. This fixture comes in a large variety of wattage and lumen package offerings and is DLC Listed (see specifications below).

FEATURES

- High reflectance optical engine delivers main beam focus through the optically designed acrylic lens
- Linear ribbed acrylic lens with Lumieo overlay manages the balance of efficiency and aesthetics
- Reflector distributes light through both optical elements
- Linear arrayed LED modules provide soft, but effective illumination

SPECIFICATIONS

HOUSING: Low profile body with matte white sloped side members

DIRECT OPTICAL COMPONENT: High reflectance optical engine

DIFFUSER SURROUND: Linear ribbed acrylic lens with Lumieo

REFLECTOR

High reflectance white reflector

LUMINAIRE TYPE

Recessed troffer fixture body assembly

Available: 2'x2' and 2'x4' size

ORDERING INFORMATION: 2X2 HSL LXT STANDARD

Example: HSL LXT22LZ28W3500LDMV40K

HSL LXT	22L	Z28W3500L	DMV	40K	EM
Series	Size	Wattage & Lumens	Driver	Color Temperature	Options
HSL LXT	22L = 2X2	<p>*Z20W2450L 20 System Watts, 2450 Delivered Lumens</p> <p>*Z24W3000L 24 System Watts, 3000 Delivered Lumens</p> <p>*Z28W3500L 28 System Watts, 3500 Delivered Lumens</p> <p>*Z32W3900L 32 System Watts, 3900 Delivered Lumens</p> <p>*Z36W4200L 36 System Watts, 4200 Delivered Lumens</p>	DMV 0-10V Dimming	<p>30K 3000K</p> <p>35K 3500K</p> <p>40K 4000K</p> <p>50K 5000K</p>	EM - Emergency Battery



HSL LXT 2X4

NGF 'Recessed with Lens

ORDERING INFORMATION: 2X4 HSL LXT STANDARD

Example: HSL LXT24LZ40W5200LDMV40K

HSL LXT	24L	Z40W5200L	DMV	40K	EM
Series	Size	Wattage & Lumens	Driver	Color Temperature	Options
HSL LXT	24L = 2X4	<p>*Z28W3600L 28 System Watts, 3600 Delivered Lumens</p> <p>*Z35W4550L 35 System Watts, 4550 Delivered Lumens</p> <p>*Z40W5200L 40 System Watts, 5200 Delivered Lumens</p> <p>*Z45W5800L 45 System Watts, 5800 Delivered Lumens</p> <p>*Z50W6450L 50 System Watts, 6450 Delivered Lumens</p> <p>*Z55W6950L 55 System Watts, 6950 Delivered Lumens</p> <p>*Z60W7350L 60 System Watts, 7350 Delivered Lumens</p>	DMV 0-10V Dimming	<p>30K 3000K</p> <p>35K 3500K</p> <p>40K 4000K</p> <p>50K 5000K</p>	EM - Emergency Battery

END PROFILE

